

Gulf Coast Paint Mfg., Inc.

High Performance Floor Coatings

PC-1703 100% Solids Epoxy

A low viscosity penetrating primer. Recommend as a primer under CT-332 and CT-352. The clear can be used as a 2-coat primer / finish system.

PC-1820 100% Solids Epoxy High Build Clear

A resin for Color Quartz floors, decorative toppings, broadcast flake, Metallic Additives, and other flooring systems. Can be used as a primer and finish coat.

CM-15 High Solids Epoxy Mastic

Used as a basecoat for our flake flooring system. Available in a Low Temp / Fast Cure for fast recoat (4 hours at 75°F).

PC-1850 100% Solids Epoxy

Ideal as a pigmented topcoat over PC-1703 or PC-1820. PC-1850 is an excellent choice for commercial areas or areas where no odor is allowed.

PC-1875 100% Solids Chemical Resistant Epoxy

Has excellent chemical resistance to acids, caustics, salts, and most solvents. Very similar to PC-517, but is self-leveling and 100% solids.

CT-332/ CT-352 Polyester Polyurethane

Ideal as a topcoat for floors in heavy traffic areas. Has excellent abrasion and impact resistance and is resistant to hot tire pickup. Note: CT-332 has fast cure version that dries in 4 hours at 75°F.

CF-621 100% Solids Joint Filler

Designed for control and saw cut joints for interior slabs only.

PC-1000 100% Solids Epoxy Repair Kit

A chemical resistant mortar designed for patching, filling and repairing spalled concrete surfaces.

Gulf Coast Paint Mfg., Inc.

High Performance Floor Coatings



WAREHOUSE FLOOR

PC-1703 100% SOLIDS EPOXY
CT-352 POLYESTER POLYURETHANE



MARINA SHOWROOM FLOOR

PC-1703 100% SOLIDS EPOXY
CT-352 POLYESTER POLYURETHANE



GARAGE FLOOR

PC-149 EPOXY PRIMER
CM-15 EPOXY MASTIC
CT-332 CLEAR



INDUSTRIAL FLOOR

PC-1703 100% SOLIDS EPOXY
PC-1850 100% SOLIDS EPOXY



AUTOMOTIVE FLOOR

PC-1703 100% SOLIDS EPOXY
CT-352 POLYESTER POLYURETHANE

30075 County Road 49, Loxley, AL 36551
email: info@gulfcoastpaint.com www.gulfcoastpaint.com
Phone: 251-964-7911