

GULF COAST PAINT MFG., INC.

PC-2.8 QUICK DRY EPOXY PRIMER

PRODUCT DESCRIPTION

Poly-Chemcure PC-2.8 is a high performing, very fast recoat, sandable, two component Amine Cured Epoxy Primer that can be applied at temperatures as low as 35°F and will cure at temperatures down to 20°F. It provides excellent adhesion and protection on properly prepared carbon steel, galvanized steel and aluminum surfaces.



Poly-Chemcure PC-2.8 @ 2 mils DFT can be recoated in 60 minutes at 90°F and 105 minutes at 75°F. PC-2.8 is sandable in 4 hours at 90°F and 5 hours at 75°F.

PRODUCT USES

Poly-Chemcure PC-2.8 is an excellent product primer for fleet, rail, construction equipment, transportation equipment and many OEM applications. PC-2.8 is an ideal epoxy primer for structural steel, tanks, vessels and equipment. For use in chemical processing plants, pulp and paper mills, fertilizer plants, petroleum refineries, electric generating stations, coal handling operations and food processing plants where recoating in 60-105 minutes is desired for maximum productivity.



- Can be applied at temperatures as low as 35°F.
- Will cure at temperatures down to 20°F.
- VOC Conforming 2.8 lbs/gal. – 335 gms/ltr – low HAPS.

PRODUCT FEATURES

- Has no induction time and a longer pot life that will improve productivity.
- Smooth, sandable primer, at 2 mils DFT, that will give maximum appearance when topcoated.
- High build primer, up to 6 mils DFT, over abrasive blasted or power tool cleaned substrate where additional corrosion resistance is needed.
- Can be applied by brush and roller in addition to spraying.

30075 County Road 49, Loxley, AL 36551

Phone: 251-964-7911

email: info@gulfcoastpaint.com

www.gulfcoastpaint.com