GULF COAST PAINT MFG., INC. PC-517 EPOXY MASTIC



A VERY HIGH CHEMICAL RESISTANT FLAKE FILLED EPOXY MASTIC

A high performing two component, high solids, high build, cycloaliphatic polyamine cured Epoxy that can be applied at 15 mils dry in one coat on vertical surfaces. This unique coating has excellent chemical, abrasion, impact and weather resistance with outstanding adhesion to marginally prepared surfaces as well as clean blasted surfaces. PC-517 Epoxy is also available in a Low Temp Cure down to 20°F.



PRODUCT FEATURES

- ✓ Self Priming on steel
- ✓ Can be applied on damp surfaces
- ✓ Cures down to 40°F. (Low temp PC-517 cures down to 20°F)
- Excellent chemical resistance to acids, caustics and many solvents
- Performs well over epoxy mortars and properly primed concrete surfaces
- Excellent as a secondary containment coating
- ✓ Excellent as a coating for internal tank linings*
- Meets all EPA and air pollution regulations.
 V.O.C. 72 GMS/Liter
- ✓ Outstanding impact and abrasion resistance



Phone: 251-964-7911

PRODUCT USES

Recommended for structural steel, concrete containment, concrete clarifiers, tank linings, vessels, equipment, pipe racks, storage tanks, towers, in chemical processing plants, pulp and paper mills, sewage and waste water treatment facilities, fertilizer plants, refineries, electric generating stations, coal handling sites, mines and marine installations.

*For use in internal tank linings, contact Gulf Coast Paint for recommendation.

30075 County Road 49, Loxley, AL 36551

email: info@gulfcoastpaint.com www.gulfcoastpaint.com